

GCCS/DII COE System Integration Support

DII COE Segment System Administrator's Manual (for WEBBr Version 3.0.0.0)

February 5, 1997

Prepared for:

DISA/JEJA
ATTN: Claire Burchell
45335 Vintage Park Plaza
Sterling, VA 20166-6701

Contract Number: DCA100-94-D-0014

Delivery Order Number: 330, Task 6

CDRL Number: A005

Prepared by:

Computer Sciences Corporation
Defense Enterprise Integration Services
Four Skyline Place
5113 Leesburg Pike, Suite 700
Falls Church, VA 22041

THIS DOCUMENT IS UNCLASSIFIED

Defense Information Infrastructure (DII)
Common Operating Environment (COE)

System Administration Manual
Netscape Web Browser (WEBBr)
Version 3.0.0.0 (HP-UX 9.07/Solaris 2.4/Solaris 2.5.1)

February 5, 1997

Prepared for:

DISA/JEJA
ATTN: Claire Burchell
45335 Vintage Park Plaza
Sterling, VA 20166-6701

Prepared by:

Computer Sciences Corporation
Defense Enterprise Integration Services
Four Skyline Place
5113 Leesburg Pike, Suite 700
Falls Church, VA 22041

Table of Contents

Preface	ii
1. Netscape Web Browser (WEBBr)	1
1.1 E-Mail	1

Preface

The following conventions are used in this document:

Bold	Used for information that is typed, pressed, or selected in executables and instructions. For example, select connect to host .
<i>Italics</i>	Used for file names, directories, scripts, commands, user IDs, document names, and Bibliography references; and any unusual computerese the first time it is used in text.
<u>Underline</u>	Used for emphasis.
Arrows <>	Used to identify keys on the keyboard. For example <Return>.
“Quotation Marks”	Used to identify informal, computer-generated queries and reports, or coined names; and to clarify a term when it appears for the first time. For example “Data-Generation Report.”
Courier Font	Used to denote anything as it appears on the screen or command lines. For example <code>tar xvf dev/rmt/3mm</code>
Capitalization	Used to identify keys, screen icons, screen buttons, field, and menu names.

1. Netscape Web Browser (WEBBr)

Netscape uses a shell wrapper to establish an environment upon invocation. Clicking on the icon executes the *WEBBr/bin/WEBBr_netscape.init* script. This script sets environment variables and then calls *WEBBr/BIN/netscape* (the netscape binary is placed in a separate directory to avoid having to rename it). First-time users will have a *~/netscape* directory created for them and a netscape preferences file is placed in that directory. The skeleton for the preferences file is located in the *WEBBr/lib* directory. As system administrator, you may wish to edit that skeleton file.

NOTE: Java is enabled with this release of the segment. A class library named *java_30* has been added to the */lib* sub-directory of this segment.

To cause WEBBr to be used as the e-mail client, the installation modifies */etc/dt/appconfig/types/C/dtwm.fp*. If the user has a front panel configuration file in their home directory (*~/dt/types/dtwm.fp* or *~/dt/types/dtwm_root.fp*) or if the system is configured to look somewhere other than */etc/dt* for the front panel configuration, then clicking on the envelope icon on the front panel will not invoke WEBBr.

1.1 E-Mail

To ensure that incoming mail can be properly accessed by Netscape users who have selected the Built-in Movemail option, the following must be done:

- C Make sure that permissions for the mail spool directory (i.e., */var/mail* for Sun platforms and */usr/mail* for HP platforms) of your installation machine have been set properly (permissions should be set to *rw-rw-rw-* or *01777*).
- C Make sure that the \$MAIL environment variable for each user is set to the mail directory for that user (e.g., the \$MAIL environment variable for user *sysadmin* should be set to */var/mail/sysadmin* on a Sun machine).

This page intentionally left blank.